- 4	Issue Date	Pages	Title	Document ID	Current OR	Current XRef
П	20030,403	16	crystal display device	US 20030063057 A1	345/87	
2	20021205	108	Display device method of driving same and electronic device mounting same	US 20020180673 A1	345/87	
m	20021003	13	Variable transmittance birefringent device	US 20020140884 A1	349/113	
4	20020613	17	COLOR LIQUID CRYSTAL DISPLAY	US 20020070911 A1	345/88	
ις.	20020124	75	Driving method of image display device, driving device of image display device, and image display device	US 20020008688 A1	345/98	
9	20011227	21	Optical element, optical light source unit and optical display device equipped with the optical light source unit	US 20010055208 A1	362/260	349/115; 362/26; 362/293; 362/31; 362/318
_	20011018	15	Liquid crystal display and projector using the same	US 20010030723 A1	349/113	
ω	20011011	16	Liquid crystal display	US 20010028430 A1	349/139	
<u></u>	20030429	16	Liquid crystal display and projector using the same	US 6556267 B2	349/129	349/130

	Issue Date	Pages	Title	Document ID	Current OR	Current XRef
10	20021217	7 7 8	Liquid crystal apparatus	US 6496170 B1	345/87	/ 110 / 200 / 201 / 201 / 201 / 200 / 300 / 300 / 300 / 300
11	20021210	45	assembly ther s	US 6493128 B1	359/265	244/129.3; 349/16; 359/241; 359/275; 52/204.5
12	20021203	15	Vertical alignment liquid crystal display having improved driving voltage control	US 6490013 B2	349/33	345/94
13	20020514	44	Spatial light modulator and a method for driving the same	US 6388649 B1	345/89	345/94; 345/97
14	20020409	23	Liquid crystal display device having reflective electrodes for controlling the azimuth of the liquid crystal	US 6369870 B1	349/130.	349/113; 349/181
15	20011016	17	Liquid crystal display having an off driving voltage greater than either zero or an optical characteristics changing voltage	US 6304304 Bl	349/33	345/94

16 20010710 17 20010213 18 20000912 20 20000905 20 20000801 21 20000321		53				
			dısplay apparatus	US 6259426 B1	345/581	744
		14	l display and ng the same	US 6188456 B1	349/113	349/130; 349/131
	~	22	tering type liquid splay device, and driving it	US 6118422 A	345/94	45/87
	0.5	10	Vertically aligned liquid crystal display	US 6115100 A	349/181	49/130; 49/143
	0.1	11	liquid	US 6097466 A	349/143	729 129 122 122
	21	48	Chromogenic window assembly construction and other chromogenic devices	US 6039390 A	296/211	/21 /16 /71 /86
22 20000314		20	Active matrix liquid crystal display for projection system	US 6038004 A	349/44	49/1 49/3 49/4 49/4 59/3
23 20000314	314	09	Bistable nematic liquid crystal which remains tilted in first and second states and which is tilted according to driving voltage	US 6038001 A	349/33	345/89; 345/95; 345/96; 349/177; 349/85
24 199911	.23	36	ng a t blocks apparatus jister	US 5990857 A	345/98	345/100; 345/204; 345/213
25 19970617	517	44	Liquid crystal device with the retardation of the liquid crystal layer greater than lambda./2 and a method for driving the same	US 5640259 A	349/33	349/177

	Issue Date	Pages	Title	Document ID	Current OR	Current XRef
26	19970128	58	Display apparatus	US 5597223 A	353/97	349/61; 353/101
27	19960521	55	apparatus with a e aperture stop means side of the modulator	US 5519518 A	349/57	349/62
28	19951212	18	rmation lement and a ht converting	US 5475213 A	250/214LA	369/284
29	19951024	18	devi fron harg	US 5461397 A	345/102	45/545/5/6
30	19950620	12	Aberration correction method and aberration correction apparatus	US 5426521 A	359/9	359/29; 359/32; 359/559
31	19950613	84	Method of driving liquid-crystal display elements	US 5424753 A	345/94	സ്യ
32	19940705	19	Optical calculating apparatus	US 5327274 A	359/107	349/17; 359/254; 359/259
33	19911029	. 12	ectric liquid c having opposin d alignment fil the liquid cry twisted and tw states which c riving method t	US 5061044 A	349/133	345/89; 345/97; 349/128; 349/37
34	19881004	<u></u>	Driving circuit of a liquid crystal display panel which equivalently reduces picture defects	US 4775861 A	345/93	345/206; 345/92; 349/54
	***************************************	***************************************		,		

	Issue Date	Pages	Title	Document ID	Current OR	Current XRef
5	19871006	47	Image processor	US 4697910 A	399/51	347/129; 347/131; 358/300; 399/5
9	19851217		13 Liquid crystal composition	US 4559161 A	252/299.63	252/299.01; 252/299.64; 252/299.65; 252/299.66; 349/170

	Issue Date	Pages	Title	Document ID	Current OR	Current XRef
	20011011	16	Liquid crystal display	US 20010028430 A1	349/139	
2	20021203	15		US 6490013 B2	349/33	345/94
m	20011016	17	Liquid crystal display having an off driving voltage greater than either zero or an optical characteristics changing voltage		349/33	345/94
4	19951024	18	Display device with a light shutter front end unit and gas discharge back end unit	US 5461397 A	345/102	345/5; 345/66

BRS L1 27688 driving near L2 L2 L2 L2 L2 L2 L2 L		Туре	#	Hits	Search Text	DBs
BKS L2 15270 pixel near electrode USPAT; US-19P; JPO; JPO; JPO; JPO; JPO; JPO; JPO; JP	H	BRS	L1	27688		USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
BRS L3 1925 color adj LCD USPAT; US-1 BRS L4 48 1 and 2 and 3 EPO; JPO; 1 BRS L7 3110 display adj EPO; JPO; 1 BRS L8 13 3 and 7 EPO; JPO; 1 BRS L9 110 RGB and 7 EPO; JPO; 1 BRS L1 10 1 and 9 EPO; JPO; 1 BRS L10 1 and 9 EPO; JPO; 1 BRS L10 1 and 9 EPO; JPO; 1 BRS L1 617 transmittance EPO; JPO; 1 BRS L12 3 7 and 11 EPO; JPO; 1 BRS L12 3 7 and 11 EPO; JPO; 1 BRS L13 185 maximum and 11 EPO; JPO; 1 BRS L13 185 maximum and 11 EPO; JPO; 1 BRS L14 4 3 and 13 BRD; 10B; 1	2	BRS	L2		pixel near electrode	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
BRS L4 48 1 and 2 and 3 and 3 election of electrodes USPAT; US-1EM, TDB BRS L7 3110 display adj electrodes EPO; JPO; IBM TDB BRS L8 13 3 and 7 EPO; JPO; IBM TDB BRS L10 10 1 and 9 EPO; JPO; IBM TDB BRS L11 617 control near EPO; JPO; IBM TDB BRS L12 3 7 and 11 EPO; JPO; IBM TDB BRS L12 3 7 and 11 EPO; JPO; IBM TDB BRS L13 185 maximum and 11 EPO; JPO; IBM TDB BRS L13 185 maximum and 11 EPO; JPO; IBM TDB BRS L14 4 1 and 13 EPO; JPO; IBM TDB	m	BRS		92	adj	; US- JPO; JDB
BRS L7 3110 display adj electrodes EPO; JPO; EPO; JPO; EPO; JPO; IBM_TDB BRS L8 13 3 and 7 EPO; JPO; IBM_TDB BRS L10 10 1 and 9 EPO; JPO; IBM_TDB BRS L11 control near EPO; JPO; IBM_TDB BRS L11 control near EPO; JPO; IBM_TDB BRS L11 and 11 EPO; JPO; IBM_TDB BRS L12 3 7 and 11 EPO; JPO; IBM_TDB BRS L13 185 maximum and 11 EPO; JPO; IBM_TDB BRS L13 185 maximum and 11 EPO; JPO; IBM_TDB BRS L14 4 3 and 13 EPO; JPO; IPO; IBM_TDB	4	BRS	Ъ4	48	and 2 and	; US- JPO; IDB
BRS L8 13 3 and 7 USPAT; US- IBM_TDB BRS L9 110 RGB and 7 EPO; JPO; IBM_TDB BRS L10 10 1 and 9 EPO; JPO; IBM_TDB BRS L11 617 control near transmittance EPO; JPO; IBM_TDB BRS L12 3 7 and 11 EPO; JPO; IBM_TDB BRS L13 185 maximum and 11 EPO; JPO; IBM_TDB BRS L14 4 3 and 13 EPO; JPO; IBM_TDB	വ	BRS	Т7	3110	display adj electrodes	us-
BRS L9 110 RGB and 7 EPO; JPO; IBM TDB BRS L10 10 1 and 9 EPO; JPO; IBM TDB BRS L11 617 transmittance IBM TDB BRS L12 3 7 and 11 EPO; JPO; IBM TDB BRS L13 185 maximum and 11 EPO; JPO; IBM TDB BRS L14 4 3 and 13 EPO; JPO; IBM TDB BRS L14 4 3 and 13 EPO; JPO; IPO; IBM TDB	9	BRS	Г8	13	and	us- o;
BRS L10 10 1 and 9 EPO; JPO; IBM_TDB BRS L11 617 transmittance transmittance iBM_TDB USPAT; US-IBM_TDB BRS L12 3 7 and 11 EPO; JPO; IBM_TDB BRS L13 185 maximum and 11 EPO; JPO; IBM_TDB BRS L14 4 3 and 13 EPO; JPO; IBM_TDB BRS L14 4 3 and 13 EPO; JPO; IBM_TDB	7	BRS	19	110	and	US- 20; 3
BRS L11 617 control near transmittance EPO; JPO; LPO; LPO; LI2 IBM_TDB BRS L12 3 7 and 11 EPO; JPO; LBM_TDB BRS L13 185 maximum and 11 EPO; JPO; LBM_TDB BRS L14 4 3 and 13 EPO; JPO; LBM_TDB BRS L14 4 3 and 13 EPO; JPO; LBM_TDB	8	BRS	110	10	and	; US- JPO; JDB
BRS L12 3 7 and 11 EPO; JPO; IBM_TDB BRS L13 185 maximum and 11 EPO; JPO; IBM_TDB BRS L14 4 3 and 13 EPO; JPO; IBM_TDB BRS L14 4 3 and 13 EPO; JPO; IBM_TDB	6	BRS	L11	617	control near transmittance	r; us- JPO; IDB
BRS L13 185 maximum and 11 EPO; JPO; JPO; IBM_TDB BRS L14 4 3 and 13 EPO; JPO; IBM_TDB BRS L14 4 3 and 13 EPO; JPO; IBM_TDB	10	BRS	L12	3	and 1	I; US- JPO; IDB
BRS L14 4 3 and 13 EPO; JPO; IBM_TDB	111	BRS	L13	ω	and	r; JP IDB
	12	BRS	L14	, 4	and 1	CP CP TDB